

## Drylining Beads

These beads provide the plasterer with the ability to produce true straight edges in drylining applications and give an excellent key for thin coat (skim) plastering. The fixing of all these products is simple and the beads give good resistance to cracking, chipping and impact damage on corners and edges.



## Product

### GPS Galvanised Dry Wall Stop Bead

A bead to protect thin coat plaster at edges and reveals and for abutment of thin coat plaster against other wall finishes. Also sometimes used as an arch bead. The GPS is a rigid but light bead perforated for an excellent thin coat plaster key.

Nail holes for easy fix with drywall nails.

Internal use only.

Sizes	Per Box:
2.4m x 3mm	50 lengths
3.0m x 3mm	50 lengths
3.0m x 6mm	50 lengths

## Storage & Protection

To prevent distortion and damage the GPS bead should be kept dry and stored above the ground on a flat surface.

Any potential corrosion in galvanised beads will only become apparent during the initial drying out period of the plaster or during periods of dampness and heavy condensation. The drying out period (which should be a maximum of 5-7 days) should be kept to a minimum.

Our GPS should be fixed using galvanised mechanical fixings at a maximum of 600mm intervals.

### Safety Precautions

GPS Galvanised Dry Wall Stop Bead is manufactured from sheared plate and strip so may contain sharp edges. Suitable personal protection should always be used when handling/installing these products.