
Plaster and Render Beads

These beads are designed to give true corners and edges to plaster and render where thick or 'rough' coats are required. Fixing is easy using plaster dabs or galvanised nails (with galvanised beads) and the mesh wings provide resistance to cracking while offering a good key to the plaster or render.



Product GWAB Galvanised Wide Angle Bead 63mm Wing

The traditional wet plaster bead provides a strong true corner or arris, with the mesh wings allowing for good plaster key and resistance to cracking. With a wider wing to allow more uneven corners and slightly deeper plaster – up to 16mm

Available in galvanised steel grade DX.51. Z275g to BS EN 10346:2009 Manufactured to BS EN 13658-1: 2005

Sizes	Per Box:
2.4m	50 lengths
3.0m	50 lengths

Storage & Information

To prevent distortion and damage the GWAB bead should be kept dry and stored above the ground on a flat surface.

Any potential corrosion in galvanised beads will only become apparent during the initial drying out period of the plaster or during periods of dampness and heavy condensation. The drying out period (which should be a maximum of 5-7 days) should be kept to a minimum.

Safety Precautions

GWAB Galvanised Wide Angle Bead is manufactured from sheared plate and strip so may contain sharp edges. Suitable personal protection should always be used when handling/installing these products.

Head Office: Vista Engineering Ltd, Carr Brook Works, Elnor Lane, Whaley Bridge, High Peak SK23 7JNTel: Sales: +44 (0) 1663 736 700Fax: +44 (0) 1663 736 710Scotland Office: Vista Engineering Ltd, 16 Barnaod Street, Rutherglen, Glasgow G73 1AHTel: +44 (0) 141 613 3144Fax: +44 (0) 141 613 3031

