

Plaster and Render Beads

These beads are designed to give true corners and edges to plaster and render where thick or 'rough' coats are required. Fixing is easy using plaster dabs or galvanised nails (with galvanised beads) and the mesh wings provide resistance to cracking while offering a good key to the plaster or render.



Product

GARB Galvanised Architrave Bead

A range of beads produced to allow for decorative finishes – i.e. shadow lines and recesses around door and window frames etc. The bead can either be supplied as an engaging bead or abutting bead with various plaster depths available.

Internal use only.

Available in galvanised steel grade DX.51. Z275g to BS EN 10346:2009
Manufactured to BS EN 13658-1: 2005

Storage & Information

To prevent distortion and damage the GARB bead should be kept dry and stored above the ground on a flat surface.

Any potential corrosion in galvanised beads will only become apparent during the initial drying out period of the plaster or during periods of dampness and heavy condensation. The drying out period (which should be a maximum of 5-7 days) should be kept to a minimum.

Sizes	Per Box:
3.0m x 10mm and 13mm engaging (without flange)	50 lengths
3.0m x 10mm, 13mm and 20mm abutting (with flange)	50 lengths

Safety Precautions

GARB Galvanised Architrave Bead is manufactured from sheared plate and strip so may contain sharp edges. Suitable personal protection should always be used when handling/installing these products.