

Security Laths

A range of laths for added security to walls, ceilings, partitions and roofs discouraging break ins via these routes. When galvanised the laths can be rendered or plastered to hide their presence.

Manufactured in accordance with BS 405: 1987 from HRPO Mild Steel to BS EN 10111: 1998



Features

- Low Profile mesh ideal for use between plasterboard and structural studs or joists to improve resistance to attack.
- Diamond shape restricts the use of hand tools for cutting
- Strands are rolled flat for uniform thickness
- Continuous mesh manufactured from a single sheet eliminates broken or weak joints.

Product

SLHDR Security Lath Heavy Duty Raised

This heavy duty raised Security Lath is ideal for internal or external brickwork and can act as a key for render or plaster finishes when galvanised.

Sheet size: 2440mm x 1220mm Mild steel or Hot dipped galvanised.

Installation

Fix at maximum 450mm centres to supporting structures

Timber stud: use 38mm galvanised staples, screws or nails with a 25mm washer.

Metal stud: use 30mm self-tapping screws with a 25mm washer

Brickwork: 50mm screw and plug with 25mm washer.

LW Aperture	SW Aperture	Width	Thickness	Weight (kg/m ²)
50.08mm	22.58mm	3.12mm	3mm	6.52

Mild Steel – Hot Rolled to BS EN 10111

Mild Steel – Hot Dip Galvanised to BS EN 1461

Safety Precautions

SSHDR Security Lath is manufactured from sheared plate and strip so may contain sharp edges. Suitable personal protection should always be used when handling/installing these products.