
SHER/ST Sheradised Square Twist Nail

Data sheet
Issue Date:
October 2023

SHER/ST Sheradised Square Twist Nail

Sherardised square twist nails to BS 1202 Part 1 are supplied in either bulk boxes of 25kg or bags of 1.25kg, approximate contents as detailed below.





Product SHER/ST

Approvals:

- CE Marked
- UKCA Marked

Product Details								
Product code	Dimensions (mm)		Approx. Box					
	D	L	Approx. Box Quantity					
SHER/ST/25KG	3.75	30	10000					
SHER/ST/1.25KG	3.75	30	500					

Fixings								
Туре	Description				f ax,k² (N/mm²)	fu 4 (N/mm²)		
А	Square twist nails - Normally supplied loose for manual fixing	Sherardized	3.4	30	4.78	600		

This diameter is the minimum cross-section dimension in accordance with EN 14592.

Square twist nails are often described in the market by their largest cross-section dimension, so that a 3.4 mm diameter nail will be sold as being 3.75 mm diameter.

In timber with a characteristic density pk of 350 kg/m³, i.e. C24 timber.

At other values of pk the value is modified so

$$f_{ax,k} = f_{ax,k} \cdot \min\left(\frac{\rho_k}{350}, 1.1\right)$$

Head Office: BPC Building Products Ltd, Flanshaw Way, Wakefield WF2 9LP Tel: 01924 364794

web: www.bpcfixings.com email: sales@bpcfixings.com

